

6. PHP log files do which of the following?
 - a. Are created by the `error_log` method.
 - b. Are updated by the `error_log` method.
 - c. Should be located in a different directory than the application.
 - d. All of these

7. Which of the following describes two-dimensional arrays?
 - a. They are similar to HTML tables. They contain rows and columns.
 - b. They should be avoided at all costs. They are inefficient and difficult to use.
 - c. They require all columns to be loaded with data before rows.
 - d. None of these.

8. Which of the following describes the first position of a two-dimensional array?
 - a. It has a subscript of 0.
 - b. It has a subscript of 1.
 - c. It has a default value.
 - d. None of these.

9. Application log files should include which of the following?
 - a. User log files.
 - b. Error log files.
 - c. Informational log files.
 - d. All of these.

10. E-mails generated because of program exceptions should do what?
 - a. Include all error information, including the error descriptions.
 - b. Include the code lines that caused the error to occur.
 - c. Include the date and time the error occurred.
 - d. All of these.

True/False

1. All exceptions should be displayed to the users.
2. The `for` loop should be used when you know exactly how many loops will occur.
3. The `while` loop will continue to loop until the conditional statement becomes true.
4. `unset` can be used to release a position in an array.
5. All PHP arrays must be declared before being used.
6. A pointer points to the location in memory that an object resides.